

# imageRUNNER ADVANCE C3530i C3525i

# imageRUNNER ADVANCE C3500 III Series

# Color | Low- to Mid-volume | Multifunction

Print up to 30 ppm (BW/color)

Scan up to 160 ipm (300 dpi) (BW/color, duplex)

Print up to 12" × 18"

2,300-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive!
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM\* systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control<sup>2</sup> utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.<sup>3</sup>



- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V<sup>2</sup> color profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.



- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-theminute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.

# SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR<sup>®</sup> certified and rated EPEAT<sup>®</sup> Gold.<sup>4</sup>

# **CONFIGURATION OPTIONS**



# SPECIFICATIONS

## Main Unit

Туре

Color Laser Multifunctional

Core Functions Standard: Print, Copy, Scan, Send, Store Ontional: Fax

Processor

Canon Dual Custom Processor (Shared)
Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

Memory 3.0 GB RAM

# Hard Disk Drive

Standard: 250 GB

#### Interface Connection

 
 Network:
 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)

 Optional:
 NFC, Bluetooth Low Energy

 Others
 USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface Paper Capacity (LTR, 20 Ib. Bond)

### Standard: 1,200 Sheets

Maximum: 2,300 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes, 100-sheet Stack Bypass

Optional: Dual 550-sheet Paper Cassettes (CASSETTE FEEDING UNIT-API)

#### Paper Output Capacity (LTR, 20 lb. Bond) Standard: 250 Sheets

Standard:	250 Sheets
Maximum:	3,450 Sheets
	(with External Finisher and Copy Tray)

#### **Finishing Capabilities**

Standard: With Inner	Collate, Group Collate, Group, Offset, Staple, Staple-Free	
Finisher:	Staple, Staple On Demand	
With External	Collate, Group, Offset, Staple, Booklet, Staple-	
Finishers:	Free Staple, Staple On Demand,	
	Hole Punch (Optional)	
Supported Media Types		

#### Supported Media Types

Paper	Thin, Plain, Recycled, Color, Heavy,
Cassettes	Pre-punched, Bond, Transparency,
(1/2):	Envelope
Stack Bypass:	Thin, Plain, Recycled, Color, Heavy,
	Pre-punched, Labels, Bond, Coated,
	Transparency, Tracing, Envelope
Cassette	
Feeding	Thin, Plain, Recycled, Color, Heavy,
Unit-AP1:	Pre-punched, Bond, Transparency

#### Supported Media Sizes

Paper	Letter, Executive, Statement-R, Envelope
Cassette 1:	[ISO-C5], Custom Size (5-1/2" x 7-1/8"
	to 11-3/4" x 8-1/2")
Paper Cassette	12" x 18", 11" x 17", Legal, Letter, Letter-R,
2:	Executive, Statement-R, Envelope
	[No.10 (COM10), Monarch, DL], Custom Size
	(5-1/2" x 7-1/8" to 12" x 18")
Stack Bypass:	12" x 18", 11" x 17", Legal, Letter, Letter-R,
	Executive, Statement, Statement-R,
	Envelope [No.10 (COM10), Monarch,
	DL, ISO-C5], Envelope Custom Size
	(3-7/8" x 3-7/8" to 12-5/8" x 18"),
	Custom Size (3-7/8" x 5-1/2" to
	12-5/8" x 18"), Free Size (3-7/8" x 5-1/2"
	to 12-5/8" x 18")5
Cassette	12" x 18", 11" x 17", Legal, Letter, Letter-R,
Feeding Unit-	Executive, Statement-R, Custom Size
AP1:	(5-1/2" x 7-1/8" to 12" x 18")

#### Supported Media Weights

Cassettes:	14 lb. Bond to 80 lb. Cover (52 to 220 g/m <sup>2</sup> )
Stack Bypass:	14 lb. Bond to 110 lb. Cover (52 to 300 g/m <sup>2</sup> )
Duplexing:	14 lb. Bond to 80 lb. Cover (52 to 220 g/m <sup>2</sup> )

#### Print/Copy Speed (BW and Color)

C3530i III:	Up to 30 ppm (Letter); Up to 20 ppm
	(Letter-R); Up to 15 ppm (Legal);
	Up to 15 ppm (11" x 17")

030251111.	(Letter-R); Up to 15 ppm (Legal); Up to 15 ppm (11" x 17")
Warm-up Time	
From Power On:	Approx. 10 Seconds <sup>6</sup>
From Sleep Mode:	Approx. 10 Seconds <sup>7</sup>
Quick Startup Mode:	Approx. 4 Seconds <sup>8</sup>
Dimensions (W	x D x H)
22-1/4" x 29-1/4"	' x 45-1/5" (565 mm x 742 mm x 1148 mm) <sup>9</sup>
Installation Spa	ace (W x D)
Basic:	Stack Bypass + Cassette Drawers open: 38-1/2" x 44-1/4" (978 mm x 1123 mm) <sup>9</sup>
Fully	
Configured:	63-3/4" x 44-1/4" (1620 mm x 1123 mm) <sup>10</sup>
Weight	
Approx 212.9 lb	(97 kg) <sup>11</sup>

Up to 25 ppm (Letter);Up to 20 ppm

Approx. 213.8 lb. (97 kg)<sup>11</sup>

## Print Specifications

**Print Resolution (dpi)** 1200 x 1200, 600 x 600

Standard Page Description Languages UFR II, PCL<sup>®</sup>6, Adobe<sup>®</sup> PS<sup>®</sup> 3

#### Direct Print

C3525i III:

Available from USB, Advanced Box, Remote UI, and Web Access<sup>11</sup>

Supported File Types PDF, TIFF, JPEG, EPS, XPS

#### Printing from Mobile Devices and

#### Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

#### Fonts PCL for

PCL fonts:	93 Roman, 10 Bitmap fonts, 2 OCR fonts,
	Andalé Mono WT J/K/S/T (Japanese,
	Korean, Simplified and Traditional Chinese), <sup>13</sup>
	Barcode Fonts <sup>14</sup>
PS fonts:	136 Roman

#### Operating System<sup>15</sup>

UFRII/PS:	Windows®/Server 2008/Windows® 7/
	Server 2008 R2/Server 2012/Windows 8.1/
	Server 2012 R2/Windows 10/Server 2016,
	MAC OS X (10.9 or later)
PCL:	Windows/Server 2008/Windows 7/Server
	2008 R2/Server 2012/Windows 8.1/Server
	2012 R2/Windows 10/Server 2016
PPD:	MAC OS X (10.3.9 or later), Windows 7/8.1/10

#### Copy Specifications

First-Copy-Out Time (LTR)

As fast as 5.9 seconds (BW)/8.2 seconds (Color)

Multiple Copies Up to 999

# Magnification

25%-400% (1% Increments)

#### Preset Reductions

#### 25%, 50%, 64%, 73%, 78%

Preset Enlargements

# 121%, 129%, 200%, 400%

# Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Twosided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

#### Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different-size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Job Done Notice, Mirror Image, Copy ID Card, Multi Sheet Feed Detection, Free Size Original, Adjust One-Touch Color, Color Balance, Area Designation, Skip Blank Pages

# Scan Specifications

#### Туре

Single-pass Duplexing Automatic Document Feeder<sup>16</sup> Document Feeder Paper Capacity

# 150 Sheets (20 lb. Bond)

#### Document Feeder Supported Media Sizes 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size: 5" x 5-1/2" to 12" x 17" (128 mm x 139.7 mm to 304.8 mm x 431.8 mm)

#### Document Feeder Supported Media Weights

 BW Original:
 13 lb. Bond to 58 lb. Cover (50 to 157 g/m²)

 Color Original:
 17 lb. Bond to 58 lb. Cover (64 to 157 g/m²)

#### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: Up to 2" (50mm), Weight: up to 4.4 lb. (2kg)]

#### Platen Maximum Scanning Size

11-3/4" x 17" (297.0 mm x 431.8 mm)

#### Pull Scan

Color Network ScanGear2 for both Twain and WIA Supported OS: Windows 7/8.1/10/ Server 2008/Server 2008 R2/ Server 2012/Server 2012 R2/Server 2016

#### Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

#### Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

#### Scan Speed (LTR)

Single-sided Scanning (BW and Color): 80 ipm (300 dpi)/51 ipm (600 dpi) Double-sided Scanning (BW and Color): 160 ipm (300 dpi)/51 ipm (600 dpi)

#### Send Specifications

# Destination

Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

#### Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

#### Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

#### **Communication Protocol**

File: Email:	FTP (TCP/IP), SMB v3.0, WebDAV SMTP, POP3
File Format	
Standard:	TIFF, JPEG, PDF (Compact, Searchable

Standard:	TIFF, JPEG, PDF (Compact, Searchable,
	Apply Policy, Optimize for Web, PDF
	A/1-b, Encrypted, Device Signature), XPS
	(Searchable, Compact, Device Signature),
	Office Open XML (PowerPoint, Word)
Optional:	PDF (Trace & Smooth, User Signature), XPS (User Signature)

#### **Universal Send Features**

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-To, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Multi Sheet Feed Detection

#### Fax Specifications

#### Maximum Number of Connection Lines

#### Modem Speed

Super G3: 33.6 Kbps G3: 14.4 Kbps

**Compression Method** MH, MR, MMR, JBIG

#### Resolution (dpi)

400 × 400, 200 × 400, 200 × 200, 200 × 100 Sending/Recording Size

Statement-R to 11" x 17"

# Fax Memory

Up to 30,000 Pages Speed Dials

# Max. 200

Group Dials/Destinations Max, 199 Dials

#### Sequential Broadcast Max. 256 Addresses

Memory Backup Yes

#### **Fax Features**

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

# **Store Specifications**

#### Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

#### Advanced Box

Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows 7/8.1/10) Concurrent Connections (Max.) SMB 64 WebDAV 3 (Active Sessions)

#### Advanced Box Available Disc Space Approx. 16 GB

# Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

#### Memory Media

Standard: USB

# Security Specifications

#### Authentication

Universal Login Manager, uniFLOW Online Standard Express,<sup>17</sup> User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in Optional: uniFLOW

#### Data

- Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup, McAfee Embedded Control<sup>2</sup> Hard Disk Drive Removal, IEEE 2600.2 Optional: Common Criteria Certification, Data
- Loss Prevention (Requires uniFLOW) Network Standard
  - Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

#### Document

Secure Watermark, Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Standard Secure Print, Digital Signature, User Signatures, Document Scan Lock Optional:

# Environmental Specifications

# Operating Environment

Temperature: 50 to 86 °F 20 to 80 % RH (Relative Humidity) Humidity:

# Power Requirements

C3530i III/ 120-127V AC 60 Hz,7.5 A C3525i III:

# Plug (Main Unit)

C3530i III/ NEMA 5-15P C3525i III:

#### **Power Consumption**

Approx. 1,500 W Maximum: Approx. 42.9 W<sup>18</sup> Standby: Sleep Mode: Approx. 0.8 W<sup>19</sup> Typical Electricity Consumption (TEC) Rating<sup>20</sup> . C3530i III: Ó.37 kWh C3525i III: 0.31 kWh

#### Standards

ENERGY STAR® Certified Rated EPEAT® Gold

#### Consumables

#### Toner GPR-53 Toner<sup>21</sup>

### Toner Yield (Estimated @ 5% Coverage)

- Black 36,000 Images Color (C,M,Y): 19,000 Images
- <sup>1</sup> Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.
- <sup>2</sup> Requires Unified Firmware Platform v3.9.
- <sup>3</sup> Requires additional option For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.
- Standard format paper (95 to 110 lb. Cover) can be supported as follows: Standard format paper size (excluding SRA3), Custom size (3-7/8" x 5-1/2" to 12" x 18"), Free size (3-7/8" x 5-1/2" to 12" x 18")
- <sup>6</sup> Time from device power-on to when copy jobs can be
- programmed with Quick Start Up mode. <sup>7</sup> Time from exiting Sleep mode to when printing is operational. <sup>8</sup> Time from device power-on to when key operation can be
- performed on the touch screen. Includes main unit and either Cassette Feeding Unit-AP1 or Cabinet Type-R.
- Includes main unit and either Cassette Feeding Unit-AP1 or Cabinet Type-R and Staple/Booklet Finisher-AA1.
   Includes main unit, ADF consumables, and Cassette Feeding
- Unit-AP1.
- <sup>12</sup> PDF print from Web sites is supported.
   <sup>13</sup> Requires the optional PCL International Font Set-A1.
   <sup>14</sup> Requires the optional Barcode Printer Kit-D1.
- Other operating systems and environments, including
- AS/400, UNIX, Linux and Citrix, may be supported. Some solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative. <sup>5</sup> Detect Feeder Multi Sheet Feed is supported. 7 No charge for this solution; however activation is required.
- Reference value (measured one unit).
- <sup>19</sup> 0.8 W sleep mode not available in all circumstances
- due to certain settings. Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.
- <sup>1</sup> GPR-53L Toner also available for Color (C, M, Y). Yield (estimated @ 5% coverage) is 8,500 images.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE C3500 III Series Specifications document.







As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. McAfee and the McAfee logo are trademarks of McAfee LLC in the US and/or other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2019 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.





TONER, CARTR & PARTS

PROTECTED



To learn about Canon's many awards, visit usa.canon.com/awards.

